




标记	页数	图号	更改内容	签名	日期




电机参数/motor parameter

电机级数/poles		8
额定电压 /rated voltage	U_N (V)	24VDC
额定功率 /rated power	P_N (W)	40
额定扭矩 /rated torque	T_N (N.m)	0.127
额定电流 /rated current	I_N (A)	2.5
额定转速 /rated speed	n_N (rpm)	3000
空载电流 /noload current	I_o (A)	0.6
空载转速 /noload speed	n_o (rpm)	4000
峰值功率 /top power	P_{top} (W)	62
峰值扭矩 /top torque	T_{top} (N.m)	0.3
峰值电流 /top current	I_{top} (A)	5
扭矩常数 /torque constant	K_t (N.m/A)	0.063
反馈装置 /feedback device	hall	
温度传感器 /temperature sensor	/	
绝缘等级 /insulation class	B	
防护等级 /protection level	IP54	
电机工作制 /rated time	S1	

Induce Voltage (CCW)



Hall output



1	黄 /yellow (crude)	U
2	蓝 /blue (crude)	V
3	绿 /green (crude)	W
4	红 /red	H+
5	黑 /black	H-
6	黄 /yellow	u
7	蓝 /blue	v
8	绿 /green	w

Technical Specification:

- Speed with gearbox (整机额定转速): 150rpm;
- Output shaft rated torque (整机额定转矩): 2.08N.m;
- Gear ratio (减速比): 1:20;
- The rotation direction of the motor shaft is the same as that of the output shaft.

未注公差	尺寸分段	0.5-3	>3-6	>6-30	>30-120	120-400	400-1000
线性尺寸	线性尺寸	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8
线性尺寸	表面圆度尺寸	±0.2	±0.5	±1	±2	±2	±2
度尺寸	尺寸分段	0.5-10	>10-50	>50-120	>120-400	>400	—
根误差	角度尺寸	±1°	±30′	±20′	±10′	±5′	—

No UL Vision

Zhejiang Linix Motor Co., Ltd.

60ZWN24-40-30-XXX/60JB20GN

设计			标准化		
审核					
工艺			批准		

阶段	标记	数量	比例
			1:1
共	张	第	张

outline drawing

借(通)用件登记	
版本号	230426
年 月 日启用	