



No.	Linear Actuator Parameters	
1	Stroke(mm)	200±5
2	Installation size(mm)	400±5
3	Voltage(v dc)	24
4	Free load speed(mm/s)	10
5	Full load speed(mm/s)	7.5
6	Dynamic load capacity(n)	5000
7	Cable thickness	twin-core 15awg
8	Cable length (mm)	1000±50
9	Front mounting end	thru hole $\phi 13$
10	Rear mounting end	thru hole $\phi 13$
11	Wire connector	tinned bare wires
12	Limit switches	Built in, unadjustable
13	Potentiometer	n/a
14	Hall sensor	n/a
15	Protection Rate	IP65
16	Free load current (amp)	≤ 1.5
17	Full load current (amp)	≤ 9

Power Wiring Diagram		
	Black	Red
Extend	-	+
Retract	+	-

A	SAMPLE ISSUE			Jeason	23.12.14		
REV.	DESCRIPTION			ECN NO.	BY	DATE	APPD. DATE
UNIT.	MM	SCALE	MATERIAL			NAME	LINEAR ACTUATOR 606E
TOL.		SHEET				DRAWING NO.	YMD606E-23121402
		1/1					
				WUXI DONGYUXIANG TECHNOLOGY CO.,LTD			