



No.	Linear Actuator Parameters	
1	Stroke(mm)	250±5
2	Installation size(mm)	450±5
3	Voltage(v dc)	24
4	Free load speed(mm/s)	5
5	Full load speed(mm/s)	3.5
6	Dynamic load capacity(n)	7000
7	Cable thickness	twin-core 15awg
8	Cable length (mm)	1000±50
9	Front mounting end	thru hole $\phi 13$
10	Rear mounting end	thru hole $\phi 13$
11	Wire connector	tinned bare wires
12	Limit switches	Built in, unadjustable
13	Potentiometer	n/a
14	Hall sensor	n/a
15	Protection Rate	IP65
16	Free load current (amp)	≤ 1.5
17	Full load current (amp)	≤ 9

Power Wiring Diagram		
	Black	Red
Extend	-	+
Retract	+	-

Confirm by customer					
Signature:			Date:		

A	SAMPLE ISSUE			Jeason	24.05.17			
REV.	DESCRIPTION			ECN NO.	BY	DATE	APPD.	DATE
UNIT.	MM	SCALE	SHEET	MATERIAL		NAME	LINEAR ACTUATOR 606E	
TOL.			1/1			DRAWING NO.	YMD606E-24051701	
Wuxi East Yu Xiang science and Technology Co., Ltd.								