



RJ45-11 straight plug




RJ45 convertor

- 1: Compliance with D level or CAT 3e standard of EIA568B and ISO/IEC11801,RJ45 connector compatible CAT5e, data transfer rate reach 10GBIT/S
- 2: Multi-style connecting modes: 1/4 bayonet connect (YT01), quickly plug/unplug(YT09/04)
- 3: Applicable for harsh environments
- 4: Cable jacket with solid diecasted shell and unique dual-clip-clip wire saddle
- 5: Sheath of cable applicable for common RJ45 plugs
- 6: Waterproof and non-waterproof design, protection level IP65 if waterproof and dustproof
- 7: Electroplated shell against wind and rain
- 8: Shielding system with high frequency noise immunity and electromagnetic interference protection



Clear push symbol



Waterproof push button



PCB switch



RJ45-10 snap plug



snap socket(dual ethernet ports IP44)



snap socket(dual ethernet port IP44)

- 1:Compliance with D level or CAT 3e standard of EIA568B and ISO/IEC11801,RJ45 connectors compatible CAT5e, data transfer rate reach 10GBIT/S
- 2:D-panel connectors, metal shell and locking system
- 3:Shielding system with high frequency noise immunity and electromagnetic interference protection
- 4:Push-pull design with secure locking system, and optional installation of straight or PCB adapter
- 5:Cable jacket with solid diecasted shell and unique dual-clip-clip wire saddle
- 6:Waterproof and non-waterproof design, protection level IP65 if waterproof and dustproof
- 7:Solid connections system can provide the solutions for data transmission in harsh environments
- 8:Not included crystal head and cable



snap socket(dual ethernet ports IP65)



snap socket(single ethernet port IP65)



straight connect



waterproof push button



PCB switch




RJ45-01 female socket

RJ45-01 male plug

- 1: Compliance with D level or CAT 3e standard of EIA568B and ISO/IEC11801,RJ45 connectors compatible CAT5e, data transfer rate reach 10GBIT/S
- 2: Multi-style connecting modes: 1/4 bayonet connect (YT01), quickly plug/unplug(YT09/04)
- 3: Applicable for harsh environments
- 4: Cable jacket with solid diecasted shell and unique dual-clip-clip wire saddle
- 5: Sheath of cable applicable for common RJ45 plugs
- 6: Waterproof and non-waterproof design, protection level IP65 if waterproof and dustproof
- 7: Electroplated shell against wind and rain
- 8: Shielding system with high frequency noise immunity and electromagnetic interference protection



RJ45-01 direct ethernet port



fireproof PBT material



RJ45 straight connect



PCB switch



Female socket (dual metal ethernet ports)

Male Plug(metal shell)

Dustproof cushion

- 1: Compliance with D level or CAT 3e standard of EIA568B and ISO/IEC11801,RJ45 connectors compatible CAT5e, data transfer rate reach 10GBIT/S
- 2: Multi-style connecting modes: 1/4 bayonet connect (YT01), quickly plug/unplug(YT09/04)
- 3: Applicable for harsh environments
- 4: Cable jacket with solid diecasted shell and unique dual-clip-clip wire saddle
- 5: Sheath of cable applicable for common RJ45 plugs
- 6: Waterproof and non-waterproof design, protection level IP65 if waterproof and dustproof
- 7: Electroplated shell against wind and rain
- 8: Shielding system with high frequency noise immunity and electromagnetic interference protection



Back



Waterproof coil clip



Patent ethernet ports



Unique CNLINKO logo



CE certification

YT-RJ45 SERIES SPECIFICATIONS SHEET

PICTURE AND PART NO.	Male plug& Female socket	Cable specification			Cable specification			Cable specification	
		0.15m ~ 0.2m /26-24 AWG			0.15m ~ 0.2m /26-24 AWG			0.15m ~ 0.2m /26-24 AWG	
		Φ5.5mm ~ Φ7mm			Φ5.5mm ~ Φ7mm			Φ5.5mm ~ Φ7mm	
									
YT-RJ45-CPE-01-001 RJ45-01male plug		YT-RJ45-CPE-03-001 RJ45-02male plug(metal shell)	YT-RJ45-CPE-13-001 RJ45-02male plug (plastic shell)		YT-RJ45-CPE-05-001 YT-05male plug		YT-RJ45-CPE-10-002 Snap-fastener plug		
									
YT-RJ45-JSX-01-001 RJ45-01female socket		YT-RJ45-JSX-04-001 RJ45-02female socket (dual metal ethernet ports)	YT-RJ45-JSX-02-001 RJ45-02 female socket (dual plastic ethernet ports)		YT-RJ45-JSX-10-001 02female socket (straight dual ethernet ports)	YT-RJ45-JSX-05-003 RJ45female socket (straight dual ethernet ports)	YT-RJ45-JSX-16-001 RJ45-16 female socket (straight dual ethernet ports IP65)	YT-RJ45-JSX-21-002 RJ45-21 female socket (single ethernet port IP65)	
									
YT-RJ45-JSX-04-002 RJ45 RJ45 female socket (straight dual ethernet ports)		YT-RJ45-JSX-11-001 RJ45-11 female socket (with customized SR cable)	YT-RJ45-JSX-05-002 RJ45 female socket (straight dual ethernet ports)		YT-RJ45-JSX-08-001 02RJ45 female socket (straight dual ethernet ports)	YT-RJ45-JSX-07-001 02RJ45 female socket (straight ethernet ports)	YT-RJ45-JSX-22-002 RJ45-22 female socket (dual ethernet ports IP65)	YT-RJ45-JSX-25-001 RJ45-25 female socket (single ethernet port IP65)	

Cable specification	0.15m ~ 0.2m /26-24 AWG	0.15m ~ 0.2m /26-24 AWG	0.15m ~ 0.2m /26-24 AWG
Diameter range	Φ5.5mm ~ Φ7mm	Φ5.5mm ~ Φ7mm	Φ5.5mm ~ Φ7mm
Contact diameter × number	8	8	8
Rated Current (A)	1.5A	1.5A	1.5A
Operating voltage (AC.V.rms)	1000V	1000V	1000V
Contact resistance	<30mΩ	<30mΩ	<30mΩ
Insulation resistance	> 500MΩ	> 500MΩ	> 500MΩ
Protection level	IP65/IP67	IP65/IP67	IP65/IP67
Durability	> 500times	≥500times	≥500times
Working temperature	-40°C ~ 80°C	-40°C ~ 80°C	-40°C ~ 80°C
Assembly Wire	1/4 bayonet connect Fast locking	Fast locking	Fast locking

MATERIALS

Housing, the insulating parts	High-performance engineering plastics	High-performance engineering plastics
Waterproof circle	Silica gel	Silica gel
Flammability rating	UL94-V0	UL94-V0

CONNECTION TYPE RJ45-01




CONNECTION TYPE RJ45-10 Wew




CONNECTION TYPE RJ45-02




DIMENSION FIGURE RJ45-01




Dimensions figure



PE clamping cable plug
(dimensions figure)




SX socket (dimensions figure)




Installation hole figure


DIMENSION FIGURE RJ45-05




Dimensions figure




PE clamping cable plug
(dimensions figure)




SX socket (dimensions figure)




Installation hole figure




DIMENSION FIGURE RJ45-10 New




Dimensions figure



PE clamping cable plug
(dimensions figure)



SX socket (dimensions figure)



Installation hole figure

